

TSV-SP07S HDMI SPLITTER

FCC CE RoHS



TSV-SP07S 1In 8Out HDMI Splitter

1x8 HDMI Splitter, HDCP2.2, Supports 3D, 4Kx2K@60Hz(YUV 4:4:4), 18G, HDR, EDID



Features

- 1). Simultaneously displays an Ultra Hi-Def source on up to eight Ultra HD displays.
- 2). Supports HDMI 2.0 18Gbps, HDR10, 4K@60HZ 4:4:4
- 3). Support downscaler from 4K to 1080P
- 4). Route your 4K video sources to 4K displays and 1080P displays simultaneously via downscaling
- 5). Supports resolutions up to Ultra HD 4Kx2K(3840x2160@60Hz YUV 4:4:4).
- 6). Supports three kinds of EDID handling abilities.
- 7). SupportsHDCP2.2/1.4 Compliant.
- 8). Supports 36 bit Deep Color.
- 9). Supports LPCM 7.1, DolbyTrueHD, Dolby digitalPlus, and DTS-HDMaster Audio.
- 10). Support 3D.
- 11). Bandwidth 18G.
- 12). Support HDR.
- 13). Support online firmware upgrade via Micro USB Port.
- 14). Advanced EDID management
- 15) Supports HDCP2.2/1.4 Compliant

SPECIFICATIONS

Operating Temperature Range	-5 to +40 °C(+23 to +104 °F)
Operating Humidity Range	5 to 90%RH (No Condensation)
Bandwidth frequency	18Gbps
HDCP	HDCP2.2
Input ports	1xHDMI(female)
Output ports	8xHDMI outputs(female)
Resolution outputs	up to 4Kx2K(3840x2160@60Hz YUV 4:4:4)
Dimensions(LxWxH)	247.2x110x17mm
Power consumption	5W(MAX)
Transmission Distance	15m(Maximum)over standard HDMI cable/26AWG
Net Weight	610g

Connection Diagram

