



Weatherproof Aluminium Housing
IR LED: Φ 5X36PCS IR LED working distance: 30M
SONY/SHARP/NEXTCHIP CCD
Optional :700/650/600/420TV Lines
Built-in IP66 3-Axis bracket, External lens adjusting
Lens: 2.8-12mm Manual Zoom Lens(2M pixels)
Dimension:256(W)x143(H)x86(D)mm Weight:1.6Kg

รหัส : KIR-673W30
ยี่ห้อ : TIS

Sync System	Internal
IR LED	Φ 5X36PCS
IR Series Distance	30 M
Lens	2.8-12mm Manual Zoom Lens(2M pixels)
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control
Usable Illumination	0.001 Lux/F2.0
S/N Ratio	≥ 48 dB (AGC OFF)
Gamma Correction	0.45
Video Out	Composite Signal (1.0Vp-p, 75 Ω)
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
White Balance	Auto
Power Source	DC12V 1000mA
Dimension	256(W)x143(H)x86(D)mm

