

TSV14

TIS TSV14 100m 1x4 HDBaseT Splitter, HDCP2.2 compliant Support POC, Ethernet

Introduction:

1. Incorporate HDBaseT technology
2. Distribute 1 Ultra HD HDMI signal to 4 identical HDBaseT outputs, with 1x loop HDMI output
3. HDCP 2.2/1.4 compliant
4. Transmitter Distance up to 100m under 1080p, 70m under 4K
5. Support resolution to 4K@60Hz, YUV 4:2:0, VESA resolution up to 1920x1200
6. Support Dolby TrueHD, DTS-HD Master Audio
7. With wide-band Bi-Directional IR control (38 ~ 56 kHz) (IR extension from Sender to Receiver or from Receiver to Sender)
8. HDBaseT output 1 supports RS232 and Ethernet pass through
9. Support 3D
10. Support POC (Receiver powered by HDBaseT Splitter)
11. DC 12V power supply

Specifications

Operating Temperature Range	-5 to +35°C +23 to 95°F
Operating Humidity Range	5 to 90%RH (No condensation)
Video Bandwidth	10.2Gbps
Video Format Supported	Resolution up to 4K @60Hz, YUV 4:2:0 VESA resolution
Connectors	1*HDMI input 1*HDMI loop output 4*RJ45 output 2*Power DC receptacle 1*Phoenix RS232 port 2x Ethernet port
Transmission Distance	100m(1080p), 70m(4k)
Power supply	110-240V/12V DC power supply
Power Consumption	15watts
Dimension	L305*W165.2*H39.8mm
Weight	1425g

